

MR1035-1501
Application Serial No. 10/092,394
Response to Final Office Action dated 20 January 2006

AMENDMENTS TO THE CLAIMS

This Listing of Claims will replace all prior versions and listings of the Claims in the subject Patent Application:

Listing of Claims:

Claim 1 (Previously presented): A method of detecting a scene change in a digital video sequence having a plurality of frames, the method comprising:

calculating a first color weighted root mean squared (RMS) value for a first frame relative to a second frame and the second frame relative to a third frame;

calculating a first mean absolute difference (MAD) value for the first frame relative to the second frame;

determining if the first color weighted RMS value meets a first criterion;

determining if the first MAD value meets a second criterion; and

designating the second frame as a scene change frame at least partly in response to determining that both the first color weighted RMS value meets the first criterion and the first MAD value meets the second criterion.

Claim 2 (Canceled).

MR1035-1501

Application Serial No. 10/092,394

Response to Final Office Action dated 20 January 2006

Claim 3 (Original): The method as defined in claim 1, further comprising storing an I-frame designation in a file for the second frame and storing a P-frame designation for a third frame in the file.

Claim 4 (Previously presented): The method as defined in claim 1, wherein the first color weighted RMS value is based at least in part on pixel luminance values and chromaticity-blue and chromaticity-red component values of the first and second frames.

Claim 5 (Previously presented): A method of detecting a scene change in a digital video sequence having a plurality of frames, the method comprising:

calculating a first root mean squared (RMS) value for a first frame relative to a second frame and the second frame relative to a third frame, the first RMS value being defined as
$$30 \text{ RMS } (F_i, F_k) = \sqrt{\frac{1}{w} \sum_{x=1}^w \sum_{y=1}^h (Y_i(x, y) - Y_k(x, y))^2 + \frac{1}{w} \sum_{x=1}^w \sum_{y=1}^{h/2} (U_i(x, y) - U_k(x, y))^2 + \frac{1}{w} \sum_{x=1}^w \sum_{y=1}^{h/2} (V_i(x, y) - V_k(x, y))^2}$$

MR1035-1501

Application Serial No. 10/092,394

Response to Final Office Action dated 20 January 2006

where $F_{sub.i}$ is the first frame, $F_{sub.k}$ is the second frame, $F(x, y)$ denotes the (x, y) pixel in frame F , w is a frame width and h is a frame height, $Y(x, y)$ corresponds to a pixel luminance value, and $U(x, y)$ and $V(x, y)$ corresponds to chromaticity components, and w_1 and w_2 are weighting coefficients for luminosity, chromaticity-blue and chromaticity-red components correspondingly;

calculating a first mean absolute difference (MAD) value for the first frame relative to the second frame;

determining if the first RMS value meets a first criterion;

determining if the first MAD value meets a second criterion; and

designating the second frame as a scene change frame at least partly in response to determining that both the first RMS value meets the first criterion and the first MAD value meets the second criterion.

Claim 6 (Original): The method as defined in claim 5, wherein $w_1 = w_2 = 1$.

MR1035-1501

Application Serial No. 10/092,394

Response to Final Office Action dated 20 January 2006

Claim 7 (Previously presented): The method as defined in claim 5, wherein the first MAD value is calculated using luminance value and excluding chromaticity components.

Claim 8 (Previously presented): The method as defined in claim 5, wherein the first criterion is a first threshold and the second criterion is a second threshold.

Claim 9 (Original): A method of detecting a scene change in a digital video sequence, the method comprising:

calculating a second temporal derivative RMS value for a first frame relative to a second frame and the second frame relative to a third frame; and

based at least in part on the second derivative value, determining that the second frame is a scene change frame.

MR1035-1501

Application Serial No. 10/092,394

Response to Final Office Action dated 20 January 2006

Claim 10 (Original): The method as defined in claim 9, wherein the determination that the second frame is a scene change frame is further based upon a mean absolute difference value calculated using at least luminosity information for the first and the second frames.

Claim 11 (Original): The method as defined in claim 9, wherein the determination that the second frame is a scene change frame is further based upon both an RMS value meeting a first criterion and the second temporal derivative RMS value meeting a second criterion.

Claim 12 (Original): The method as defined in claim 9, wherein the second temporal derivative RMS value is greater than or equal to a first threshold.

MR1035-1501

Application Serial No. 10/092,394

Response to Final Office Action dated 20 January 2006

Claim 13 (Previously presented): A method of detecting a scene change in a digital video sequence, the method comprising:

calculating a second temporal derivative RMS value for a first frame relative to a second frame and the second frame relative to a third frame; and

based at least in part on the second derivative value, determining that the second frame is designated as a scene change frame when the second temporal derivative RMS value is negative and has a greater absolute value than a first value.

Claim 14 (Previously presented): A method of detecting a scene change in a digital video sequence, the method comprising:

calculating a first RMS value, wherein the first RMS value is color weighted;

calculating a second temporal derivative RMS value based only on temporal components for a first frame relative to a second frame and the second frame relative to a third frame; and

based at least in part on the second derivative value, determining that the second frame is a scene change frame.

MR1035-1501

Application Serial No. 10/092,394

Response to Final Office Action dated 20 January 2006

Claim 15 (Previously presented): A method of detecting a scene change in a digital video sequence, the method comprising:

calculating a second temporal derivative RMS value for a first frame relative to a second frame and the second frame relative to a third frame, the second temporal derivative RMS value being equal to $(\text{RMS}(F_{\text{sub}.i-1}, F_{\text{sub}.i}) - 2\text{RMS}(F_{\text{sub}.i}, F_{\text{sub}.i+1}) + \text{RMS}(F_{\text{sub}.i+1}, F_{\text{sub}.i+2}))$, where $F_{\text{sub}.i-1}$ is the first frame, $F_{\text{sub}.i}$ is the second frame, $F_{\text{sub}.i+1}$ is a third frame, and $F_{\text{sub}.i+2}$ is a fourth frame; and

based at least in part on the second derivative value, determining that the second frame is a scene change frame.

Claims 16-30 (Canceled).